

## Art. 562

The declaration of conformity has been issued under the sole responsibility of the manufacturer to the following importer and authorized representative in EU:

**Kintar Trading OÜ, Koplipere tee 17, Rae küla, Rae vald 75310, Harjumaa, Estonia**

which states that personal protective equipment described below

**Art. 562 – 13 gauge polyester winter gloves, double latex coating – full latex coating of the hand, second foam coating on palm and fingertips. 10 gauge thermo acrylic terry brushes lining, sizes 7 to 12**

is in conformity with the relevant Union harmonisation legislation



**REGULATION (EU) 2016/425 – on personal protective equipment**

**EN ISO 21420:2020 - General requirements and test methods for protective gloves**



**EN 388 - Protective gloves against mechanical risks (levels obtained on the palm)**

- 2: Resistance to abrasion (from 1 to 4)
- 2: Resistance to cutting (from 1 to 5)
- 4: Resistance to tear (from 1 to 4)
- 2: Resistance to puncture (from 1 to 4)
- x: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



**EN 511 - Protective gloves against cold**

- x: Protection against convective cold
- 2: Protection against contact cold
- x: Protection against water penetration



**EN 407 - Protective gloves against thermal risks (heat and/or fire)**

- x: Burning behaviour (from 1 to 4)
- 2: Contact heat resistance (from 1 to 4)
- x: Convective heat resistance (from 1 to 4)
- x: Radiant heat resistance (from 1 to 4)
- x: Resistance to small splashes of molten metal (from 1 to 4)
- x: Resistance to large quantities of molten metal (from 1 to 4)

following the EU type examination (module B) carried out by:

**CTC, Notified Body no. 0075**

who issued the EU type examination test report:

**0075/1955/162/04/20/1067**

Done at Rae, 21/07/2020  
By Roland Pärn, CEO

## TECHNICAL FILE

### DESCRIPTION

Seamless knitted polyester winter gloves with soft and comfortable double latex coated. Very warm thermo acrylic terry lining. Waterproof. Superb grip. Excellent protection against contact cold and contact heat. Contact heat results are: threshold time Tt at 100°C – around 1 min, 250°C – around 20 sec, 350°C – around 14 sec. Ideal for precision handling in wet and cold conditions while maintaining optimal dexterity. Ideal for outdoor work.

### CHARACTERISTICS

- 13 gauge polyester liner
- 10 gauge thermo acrylic lining
- full double latex coating
- elastic knitted wrist
- colours: orange / black

**SIZES** Available in sizes 7 to 12

**PRACTICAL INFORMATION**

Reference	Barcode	Color	Size	Packing quantity
56207	4741300562077	orange/black	7	6 pairs/60 pairs
56208	4741300562084	orange/black	8	6 pairs/60 pairs
56209	4741300562091	orange/black	9	6 pairs/60 pairs
56210	4741300562107	orange/black	10	6 pairs/60 pairs
56211	4741300562114	orange/black	11	6 pairs/60 pairs
56212	4741300562121	orange/black	12	6 pairs/60 pairs

**APPLICATIONS**

Wet and cold environment. Glove used for work in sectors such as:

- industry • construction • gardening • agriculture • maintenance • forestry • transport • assembly • mechanical risk jobs • shipping • logistics • fishing • general purpose • general handling

**MAINTENANCE - STORAGE**

- heavily damaged gloves will affect level of protection and should be replaced
- in the original package in a well-ventilated area away from extreme temperature

---

Kintar Trading OÜ Koplipere tee 17 Rae küla Rae vald 75310 Harjumaa Estonia tel +372 6793 080 [info@kintar.ee](mailto:info@kintar.ee) [www.kintar.ee](http://www.kintar.ee)  
VAT EE100697588 reg. 10231137