

# EU DECLARATION OF CONFORMITY

## Art. 7157

The declaration of conformity has been issued under the sole responsibility of the manufacturer to the following importer and authorized representative in EU:

Kintar Trading OÜ, Koplipere tee 17, Rae küla, Rae vald 75310, Harjumaa, Estonia

which states that personal protective equipment described below

Art. 7157 – 13 gauge UHMWPE/glass fiber/polyester/Spandex (outside) cut resistent (level D) winter gloves, double latex coating – full latex coating of the hand, second foam coating on palm and fingertips. 10 gauge thermo acrylic terry brushes lining, sizes 8 to 11

is in conformity with the relevant Union harmonisation legislation

REGULATION (EU) 2016/425 - on personal protective equipment



EN ISO 21420:2020 - General requirements and test methods for protective gloves



EN 388 - Protective gloves against mechanical risks (levels obtained on the palm) 3: Resistance to abrasion (from 1 to 4)

- x: Resistance to cutting (from 1 to 5)
- 4: Resistance to tear (from 1 to 4)
- 3: Resistance to puncture (from 1 to 4)
- D: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



## EN 511 - Protective gloves against cold

- x: Protection against convective cold
- 2: Protection against contact cold
- x: Protection against water penetration



### EN 407 - Protective gloves against thermal risks (heat and/or fire)

- x: Burning behaviour (from 1 to 4)
- 2: Contact heat resistance (from 1 to 4)
- x: Convective heat resistance (from 1 to 4)
- x: Radiant heat resistance (from 1 to 4)
- x: Resistance to small splashes of molten metal (from 1 to 4)
- x: Resistance to large quantities of molten metal (from 1 to 4

following the EU type examination (module B) carried out by: CTC, Notified Body no. 0075

who issued the EU type examination test report: 0075/1955/162/01/21/0165

Done at Rae, 21/10/2021 By Roland Pärn, CEO

## **TECHNICAL FILE**

#### DESCRIPTION

Seemless knitted cut resistant winter gloves with soft and comfortable double latex coated. Very warm thermo acrylic terry lining. Waterproof. Superb grip. Excellent protection against cut (level D), contact cold and contact heat. Contact heat results are: threshold time Tt at 100°C – around 1 min, 250°C – around 26 sec, 350°C – around 20 sec, 500°C – around 8 sec. Ideal for precision handling in wet and cold conditions while maintaining optimal dexterity. Ideal for outdoor work.

#### CHARACTERISTICS

• 13 gauge UHMWPE/glass fiber/polyester/Spandex liner • 10 gauge thermo acrylic lining • full double latex coating • elastic knitted wrist • colours: blue/black

SIZES Available in sizes 8 to 11

er gloves, D gauge

## PRACTICAL INFORMATION

Reference	Barcode	Color	Size	Packing quantity
715708	4741300715787	blue/black	8	6 pairs/60 pairs
715709	4741300715794	blue/black	9	6 pairs/60 pairs
715710	4741300715701	blue/black	10	6 pairs/60 pairs
715711	4741300715718	blue/black	11	6 pairs/60 pairs

## APPLICATIONS

Wet, risks of cut and cold environment and other mechanical risks which can be found in sectors such as:

• construction • production • manufacturing of metal structures • industry • mechanics • transport • assembly • mechanical risk jobs • logistics • fish filleting and fishing • general handling

## MAINTENANCE - STORAGE

• heavily damaged gloves will affects level of protection and should be replaced

• in the original package in a well-ventilated area away from extreme temperature

Kintar Trading OÜ Koplipere tee 17 Rae küla Rae vald 75310 Harjumaa Estonia tel +372 6793 080 <u>info@kintar.ee</u> <u>www.kintar.ee</u> VAT EE100697588 reg. 10231137